

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings of claims in the application:

**Listing of Claims:**

1                   1.       (Previously Presented) A system for use with electric equipment, the  
2 system comprising:  
3                   a housing;  
4                   a first input/output (I/O) device configured to couple to the electric equipment;  
5                   a monitor coupled to the first I/O device and configured to determine information  
6 regarding the electric equipment;  
7                   a second I/O device configured to communicate with a remote computer via a  
8 communication network, the monitor being configured to provide the information regarding the  
9 electric equipment to the communication network via the second I/O device;  
10                  a memory that stores a computer-executable program configured to be executed  
11 by the remote computer to provide a computer interface for providing indicia of the information  
12 regarding the electric equipment, the computer interface being in a format that is distinct from a  
13 network browser format; and  
14                  an interface-provisioning device coupled to the memory and the second I/O  
15 device and configured to convey the computer-executable program toward the remote computer  
16 via the second input/output device and the communication network;  
17                  wherein each of the first and second I/O devices, the monitor, the memory, and  
18 the interface-provisioning device are disposed at least partially in the housing.

1                   2.       (Previously Presented) The system of claim 1 wherein the computer-  
2 executable program is configured to provide an interface when executed.

1                   3.       (Original) The system of claim 2 wherein the computer-executable  
2 program comprises the interface application.

1                   4.       (Original)   The system of claim 2 wherein the computer-executable  
2 program is configured to obtain the interface application.

1                   5.       (Previously Presented)   The system of claim 4 wherein the computer-  
2 executable program is configured to determine whether a desired version of an interface  
3 application is stored by the remote computer and if not, then to obtain the interface application.

1                   6.       (Canceled)

1                   7.       (Previously Presented)   The system of claim 2 wherein the interface is a  
2 graphical-window-based interface.

1                   8.       (Original)   The system of claim 1 wherein the monitor and the interface-  
2 provisioning device comprise software code.

1                   9.       (Original)   The system of claim 1 wherein the system is an  
2 uninterruptible power supply system further comprising:  
3                   an AC power input configured to receive AC power;  
4                   a DC power source;  
5                   an output circuit including a power output; and  
6                   a controllable switch coupled to the AC power input, the DC power source, and  
7 the output circuit and configured to selectively couple at least one of the AC power input and the  
8 DC power source to the output circuit.

1                   10.      (Original)   The system of claim 1 wherein the monitor is configured to  
2 determine information regarding at least one of air-conditioning equipment, a smart generator, a  
3 leak detector, a power distribution unit, an environmental monitoring device, and an automatic  
4 transfer switch.

1                   11.     (Original) A computer program product residing on a computer-readable  
2 medium on a system coupled to electronic equipment, the computer program product comprising  
3 computer-readable instructions for causing a computer to:

4                   determine indications of operation of the electronic equipment; and  
5                   convey a computer-executable program to a network toward a remote device to be  
6 executed by the remote device, the computer-executable program being configured to execute an  
7 interface application to provide a user interface for providing information regarding the operation  
8 of the electronic equipment, the interface being in a format different from a network-browser  
9 format.

1                   12.     (Original) The computer program product of claim 11 wherein the  
2 computer-executable program comprises the interface application.

1                   13.     (Original) The computer program product of claim 11 wherein the  
2 computer-executable program is configured to obtain the interface application.

1                   14.     (Original) The computer program product of claim 13 wherein the  
2 computer-executable program is configured to determine whether a desired version of an  
3 interface application is stored by the remote device and if not, then to obtain the interface  
4 application.

1                   15.     (Canceled)

1                   16.     (Previously Presented) The computer program product of claim 11  
2 wherein the interface is a graphical-window-based interface.

1                   17.     (Currently Amended) An uninterruptible power supply (UPS) system  
2 comprising:  
3                   an AC power input configured to receive AC power;  
4                   a DC power source;

5                   an output circuit including a power output;  
6                   a controllable switch coupled to the AC power input, the DC power source, and  
7 the output circuit and configured to selectively couple at least one of the AC power input and the  
8 DC power source to the output circuit;  
9                   a first input/output (I/O) device configured to couple to electric equipment;  
10                  a monitor coupled to the first I/O device and configured to determine information  
11 regarding at least one of power use and power needs of the electric equipment;  
12                  a second I/O device configured to communicate with a remote computer via a  
13 communication network;  
14                  a memory that stores a computer-executable program configured to be executed  
15 by **[[a]] the** remote computer to provide a computer interface for providing indicia of the  
16 information regarding the UPS system, the computer interface being in a format that is distinct  
17 from a network browser format; and  
18                  an interface-provisioning means for conveying the computer-executable program  
19 toward the remote computer via the second input/output device and the communication network.

1                   18.     (Canceled)

1                   19.     (Previously Presented)   The system of claim 17 wherein the interface is a  
2 graphical-window-based interface.

1                   20.     (Currently Amended)   A method of providing information regarding  
2 electronic equipment, the method comprising:

3                   monitoring operation of the electronic equipment at a first device;  
4                   receiving, at the first device, an information request regarding the electronic  
5 equipment from a network browser application of a requesting device remote from the first  
6 device;

7                   attempting, at the first device, to determine whether the requesting device  
8 currently stores a desired version of a computer-executable user-interface program; and

9                   executing ~~a~~ the computer-executable user-interface program at the requesting  
10 device to produce a user interface for providing information regarding the operation of the  
11 electronic equipment, the interface being in a first format that is distinct from a second format  
12 associated with the network browser application.

1                   21.     (Canceled)

1                   22.     (Currently Amended) The method of claim ~~21~~20 further comprising  
2 transferring the computer-executable program to the requesting device if the attempting to  
3 determine fails to determine that the requesting device currently stores the desired version of the  
4 computer-executable user-interface program.

1                   23.     (Original) The method of claim 22 further comprising transferring the  
2 computer-executable program to the requesting device if the attempting to determine determines  
3 that the requesting device does not currently store the desired version of the user-interface  
4 computer-executable program.

1                   24.     (Currently Amended) The method of claim ~~21~~20 further comprising  
2 abstaining from transferring the computer-executable program to the requesting device if the  
3 attempting to determine determines that the requesting device currently stores the desired version  
4 of the computer-executable user-interface program.

1                   25.     (Original) The method of claim 24 further comprising instructing the  
2 requesting device to execute the computer-executable user-interface program stored by the  
3 requesting device.

1                   26.     (Original) The method of claim 20 further comprising:  
2                   transferring an address of a network server accessible from the remote device to  
3 the remote device; and  
4                   accessing the network server from the remote device and transferring to the  
5 remote device at least one of the computer-executable user-interface program and a computer-

executable loader program configured to determine whether a desired version of the user-interface program is stored in association with the remote device.

27. (Canceled)

28. (Previously Presented) The method of claim 20 wherein executing the user-interface program produces a graphical-window-based user interface.

29. (Original) The method of claim 20 further comprising controlling the electronic equipment by manipulating the user interface.

30. (Currently Amended) A computer program product residing on a computer-readable medium and comprising computer-readable and computer-executable instructions for causing a computer to:

execute an interface-producing program to produce a graphical-window-based user interface on a display of ~~the a~~ first device for providing information regarding the operation of the electronic equipment, **wherein the electronic equipment is monitored by a second device remote from the first device**; and

determine whether a desired version of the interface-producing program is stored in association with the first device.

31. (Original) The computer program product of claim 30 wherein the instructions are configured to cause the computer to access a remote server and download the desired version of the interface-producing program if the computer program product fails to cause the computer to determine that the desired version of the interface-producing program is stored in association with the first device.

32. (Previously Presented) The system of claim 1 wherein the interface-provisioning device is configured to convey the computer-executable program toward the remote computer via the second input/output device and the communication network in response to a

4 determination that the remote computer is not presently storing a latest version of the computer-  
5 executable program.

1                   33.     (Previously Presented) The system of claim 32 wherein the interface-  
2 provisioning device is configured to make the determination that the remote computer is not  
3 presently storing the latest version of the computer-executable program.